

## SEMI - AUTOMATIC STRAPPING MACHINE HUALIAN HIGH TABLE



| MODEL                     | PARAMETER                 |
|---------------------------|---------------------------|
| MAX. STRAP SIZE (MM)      | <b>NOT STIPULATED</b>     |
| MIN. STRAP SIZE (MM)      | <b>60 X 30</b>            |
| STRAPPING SPEED (SECONDS) | <b>1.5</b>                |
| STRAP WIDTH (MM)          | <b>9/12/15</b>            |
| STRAP FORCE (NEWTON)      | <b>450</b>                |
| WORKING TABLE HEIGHT (MM) | <b>750</b>                |
| POWER SOURCE (V/HZ)       | <b>220 / 50, ¼ HP</b>     |
| EXTERNAL DIMENSION (MM)   | <b>L900 X D580 XH 750</b> |
| WEIGHT (KG)               | <b>100</b>                |

## SEMI - AUTOMATIC STRAPPING MACHINE HUALIAN LOW TABLE



| MODEL                     | PARAMETER                 |
|---------------------------|---------------------------|
| MAX. STRAP SIZE (MM)      | <b>NOT STIPULATED</b>     |
| MIN. STRAP SIZE (MM)      | <b>60 X 30</b>            |
| STRAPPING SPEED (SECONDS) | <b>1.5</b>                |
| STRAP WIDTH (MM)          | <b>9/12/15</b>            |
| STRAP FORCE (NEWTON)      | <b>450</b>                |
| WORKING TABLE HEIGHT (MM) | <b>500</b>                |
| POWER SOURCE (V/HZ)       | <b>220 / 50, ¼ HP</b>     |
| EXTERNAL DIMENSION (MM)   | <b>L900 X D580 X H500</b> |
| WEIGHT (KG)               | <b>90</b>                 |

## SEMI - AUTOMATIC STRAPPING MACHINE REGULAR HIGH TABLE



| MODEL                     | PARAMETER                 |
|---------------------------|---------------------------|
| MAX. STRAP SIZE (MM)      | <b>NOT STIPULATED</b>     |
| MIN. STRAP SIZE (MM)      | <b>60 X 30</b>            |
| STRAPPING SPEED (SECONDS) | <b>1.5</b>                |
| STRAP WIDTH (MM)          | <b>9/12/15</b>            |
| STRAP FORCE (NEWTON)      | <b>450</b>                |
| WORKING TABLE HEIGHT (MM) | <b>750</b>                |
| POWER SOURCE (V/HZ)       | <b>220 / 50, ¼ HP</b>     |
| EXTERNAL DIMENSION (MM)   | <b>L900 X D580 X H750</b> |
| WEIGHT (KG)               | <b>90</b>                 |

## SEMI - AUTOMATIC STRAPPING MACHINE REGULAR LOW TABLE



| MODEL                     | PARAMETER          |
|---------------------------|--------------------|
| MAX. STRAP SIZE (MM)      | NOT STIPULATED     |
| MIN. STRAP SIZE (MM)      | 60 X 30            |
| STRAPPING SPEED (SECONDS) | 1.5                |
| STRAP WIDTH (MM)          | 9/12/15            |
| STRAP FORCE (NEWTON)      | 450                |
| WORKING TABLE HEIGHT (MM) | 500                |
| POWER SOURCE (V/HZ)       | 220 / 50, ¼ HP     |
| EXTERNAL DIMENSION (MM)   | L900 X D580 X H500 |
| WEIGHT (KG)               | 80                 |

## SEMI - AUTOMATIC STRAPPING MACHINE CHALI TAIWAN HIGH TABLE



| MODEL                | PARAMETER       |
|----------------------|-----------------|
| CYCLE TIME           | 1.5 SEC/STRAP   |
| TENSION RANGE        | 15-45 KG        |
| SEALING METHOD       | HEATING ELEMENT |
| STRAP WIDTH (MM)     | 9/12/15         |
| REEL INSIDE DIAMETER | 200MM           |
| TABLE HEIGHT         | 780MM           |
| POWER SUPPLY         | 220 / 50/1HP    |
| POWER CONSUMPTION    | 0.5 KW          |

## SEMI - AUTOMATIC STRAPPING MACHINE CHALI TAIWAN LOW TABLE



| MODEL                | PARAMETER       |
|----------------------|-----------------|
| CYCLE TIME           | 1.5 SEC/STRAP   |
| TENSION RANGE        | 15-45 KGS       |
| SEALING METHOD       | HEATING ELEMENT |
| STRAP WIDTH (MM)     | 9/12/15         |
| REEL INSIDE DIAMETER | 200MM           |
| TABLE HEIGHT         | 500MM           |
| POWER SUPPLY         | 220 / 50/1HP    |
| POWER CONSUMPTION    | 0.5 KW          |

## SEMI - AUTOMATIC STRAPPING MACHINE FEATHER TOUCH



| MODEL                     | PARAMETER              |
|---------------------------|------------------------|
| MAX. STRAP SIZE (MM)      | NOT STIPULATED         |
| MIN. STRAP SIZE (MM)      | 60 X 30                |
| STRAPPING SPEED (SECONDS) | 1.5                    |
| STRAP WIDTH (MM)          | 6/12/15                |
| STRAP FORCE (NEWTON)      | 450                    |
| WORKING TABLE HEIGHT (MM) | 500                    |
| POWER SOURCE (V/HZ)       | 220 / 50, ¼ HP         |
| EXTERNAL DIMENSION (MM)   | L900 X D580 X H750/500 |
| WEIGHT (KG)               | 85                     |

## SEMI - AUTOMATIC STRAPPING MACHINE 2.5 MM HEAVY TOP



| MODEL                        | PARAMETER              |
|------------------------------|------------------------|
| STRAPPING SPEED (SECONDS)    | 1.5                    |
| STRAP WIDTH (MM)             | 9 /12/15               |
| STRAP FORCE (NEWTON)         | 450                    |
| WORKING TABLE THICKNESS (MM) | 750                    |
| TABLE TOP THICKNESS (MM)     | 2.5                    |
| HOUSING                      | IRON ROLLER            |
| HEAVY MOTOR                  | COPPER                 |
| MICRO SWITCH                 | HUIDA                  |
| PCB CARD                     | PACKWAY                |
| POWER SOURCE (V/HZ)          | 220 / 50, ¼ HP         |
| EXTERNAL DIMENSION (MM)      | L900 X D580 X H750/500 |
| WEIGHT (KG)                  | 100                    |

## SEMI - AUTOMATIC STRAPPING MACHINE DOUBLE MOTOR



| MODEL                               | PARAMETER                    |
|-------------------------------------|------------------------------|
| STRAP WIDTH                         | <b>9/12/15 MM</b>            |
| SPEED                               | <b>1.5 SEC/ STRAPS</b>       |
| POWER SUPPLY                        | <b>220 V SINGLE PHASE</b>    |
| POWER CONSUMPTION                   | <b>0.65 KW</b>               |
| MACHINE DIMENSION (L * W * H)<br>MM | <b>L895 * D565 * H735 MM</b> |
| WEIGHT (KG)                         | <b>75 KG</b>                 |

## SEMI - AUTOMATIC ARCH TYPE STRAPPING MACHINE



| MODEL                               | PARAMETER          |
|-------------------------------------|--------------------|
| PP BELT WIDTH                       | 9 - 12 MM          |
| SPEED                               | 1.5 M / S          |
| POWER SUPPLY                        | 220 V / 50 HZ      |
| POWER                               | 350 W              |
| MACHINE DIMENSION (L * W * H)<br>MM | 770 X 540 X 970 MM |
| PP BELT THICKNESS                   | 0.6 -0.8 MM        |
| FRAME SIZE                          | 355 X 210 MM       |

## BATTERY POWERED SEMI - AUTOMATIC STRAPPING MACHINE



| MODEL          | PARAMETER  |
|----------------|--|
| DIMENSION      | WIDTH - 610 MM, DEPTH - 545 MM, HEIGHT - 750 MM.         |
| WEIGHT         | 55 KG  |
| PACKAGE SIZE   | MINIMUM - W X H (MM)- 100 X 30 MM<br>MAXIMUM - UNLIMITED |
| SEALING METHOD | HEAT SEAL  |
| TENSION SYSTEM | TORQUE SYSTEM  |
| MAX. TENSION   | 500 N (50 KGF)   |
| STRAP WIDTH    | 5 MM - 15.5 MM   |
| STRAP COIL     | OD 450 MM X ID 200 MM X WIDTH 200 MM                     |
| POWER SUPPLY   | 180 V - 240 V 50 HZ / 60 HZ                              |
| POWER RATING   | 0.4 KW   |

## PALLET STRAPPING MACHINE



| MODEL                            | PARAMETER           |
|----------------------------------|---------------------|
| STRAP WIDTH                      | 9- 15 MM            |
| SPEED                            | 1.5 SEC/ STRAPS     |
| POWER SUPPLY                     | 220 V SINGLE PHASE  |
| POWER CONSUMPTION                | 0.65 KW             |
| MACHINE TENSION                  | 450 NEWTONS         |
| MACHINE DIMENSION (L * W * H) MM | 550 * 700 * 1300 MM |
| WEIGHT (KG)                      | 100 KG              |